



THE LATEST IN HIGH-TECHNOLOGY LUBRICATION

– ALL PRODUCTS ARE CERTIFIED AND BONDED BY THE MANUFACTURER'S 5 MILLION DOLLAR LIABILITY INSURANCE. –

SAE 10W-40



V231130

Superior Protection

- Exceeds the latest API SP standards
- Enhanced additives for longer service life

Medium Viscosity

- Less friction helps reduce oil consumption
- Thicker oil maintains a better lubricant film

Energy Efficient

- Less friction helps improve fuel economy
- Less oil consumption and exhaust emissions

Suitable for gasoline and diesel vehicles operating in moderate to hotter climates and where recommended by manufacturer.

MEETS OR EXCEEDS OEM PERFORMANCE STANDARDS

SAE GRADE	Full Synthetic	10W-40
API SERVICE		SP
API Gravity	ASTM D287	32.08
Flash Point, COC °C/°F	ASTM D92	210 / 410
Pour Point, °C/°F	ASTM D97	-33 / -27.4
Viscosity @ 40°C, cSt	ASTM D445	97
Viscosity @ 100°C, cSt	ASTM D445	15.1
Viscosity Index	ASTM D2270	165
CCS, mPa-sec °C max	ASTM D5293	5049
Total Base No. TBN	ASTM D2896	9.5

- ▶ API SP
- ▶ API SN PLUS
- ▶ API SN
- ▶ API SM
- ▶ BMW LL-O/M54
- ▶ MB 226.5
- ▶ MB 229.31
- ▶ MB 229.51
- ▶ RENAULT RN 0700
- ▶ VW 501.01
- ▶ VW 505.01

AVAILABLE IN

- ▶ 1-QUART
- ▶ 1-GALLON
- ▶ 5-QUART
- ▶ 6-GAL BAG-IN-BOX CARTON
- ▶ 5-GAL PAIL
- ▶ 55-GALLON DRUM
- ▶ BULK



Typical Characteristics Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to OTOMAX (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.