

THE LATEST IN HIGH-TECHNOLOGY LUBRICATION

– ALL PRODUCTS ARE CERTIFIED AND BONDED BY THE MANUFACTURER'S 5 MILLION DOLLAR LIABILITY INSURANCE. –

SAE 5W-40



V231130

Superior Protection

- Exceeds the latest API SP standards
- Enhanced additives for longer service life

Low Viscosity

- Less friction helps reduce oil consumption
- Faster cold weather start-up protection

Energy Efficient

- Less friction helps improve fuel economy
- Less oil consumption and exhaust emissions

Suitable for gasoline or light-duty diesel vehicles operating in moderate to warmer climates and where recommended by manufacturer.

MEETS OR EXCEEDS OEM PERFORMANCE STANDARDS

SAE GRADE	Full Syn	5W-40
API SERVICE		SP
API Gravity	ASTM D287	34.79
Flash Point, COC °C/°F	ASTM D92	205 / 401
Pour Point, °C/°F	ASTM D97	-46 / -50.8
Viscosity @ 40°C, cSt	ASTM D445	90.77
Viscosity @ 100°C, cSt	ASTM D445	14.82
Viscosity Index	ASTM D2270	171
CCS, mPa-sec °C max	ASTM D5293	6600 @ -30
Total Base No. TBN	ASTM D2896	8.4

- ▶ API SP, SN PLUS, SN, SM
- ▶ ACEA A3/B3
- ▶ ACEA A3/B4
- ▶ BMW LONGLIFE 01
- ▶ BMW LL-O/M54
- ▶ MB 226.5
- ▶ MB 229.31
- ▶ MB 229.51
- ▶ MB 229.52
- ▶ PORSCHE A40
- ▶ PSA B71 2290
- ▶ RENAULT RN 0700

- ▶ RENAULT RN 0710
 - ▶ RENAULT RN 0720
 - ▶ VW 501.01
 - ▶ VW 502.00
 - ▶ VW 505.01
- AVAILABLE IN
- ▶ 1-QUART
 - ▶ 1-GALLON
 - ▶ 5-QUART
 - ▶ 6-GAL BAG-IN-BOX CARTON
 - ▶ 5-GAL PAIL
 - ▶ 55-GAL DRUM AND BULK

Typical Characteristics Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to OTOMAX (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.